

FUSIONMASTER® HF225



Features

- Robust, reliable and low maintenance.
- Self-contained hydraulic hand pump simplifies operation.
- Compact for trench work.
- Easy one man operation.
- Joints rapidly prepared with the powerful electric Facer.
- Self-centring Fittings Chuck – simple way to hold stub flanges.
- Heater provides controlled uniform surface temperature.
- Heater achieves working temperature in approximately 15 minutes.
- Replaceable non-stick Cloth system for Heater plate reduces production downtime.
- Reducing Liners available for pipe and fittings.

(The EHF225 electric-hydraulic pump option is also available)

SPECIFICATIONS

Component Data

| | | |
|---------------------|-------------------------|--------|
| Butt Machine | 860L x 410W x 460H (mm) | 45.0kg |
| Heater Plate | 1400 W, 240 Vac | 4.0kg |
| Facer | 900 W, 240 Vac | 11.0kg |
| Fittings Chuck | | 8.0kg |
| Heater/ Facer Stand | | 5.3kg |
| Accessory Case | 740L x 340W x 300H (mm) | 12.4kg |

(Recommended generator for field use is 3.5kVA, 240V, single phase)



DIXON INDUSTRIES PTY LTD

ABN: 89 008 171 855
17 Frederick Road, Royal Park SA 5014
Tel: 61 8 8240 1555 Fax: 61 8 8240 5588
For more information visit: dixonind.com.au

FUSIONMASTER® and Dixon® are registered trademarks of Dixon Industries Pty Ltd. © Dixon Industries Pty Ltd. 2000. Revised Oct 2006